



Polaris CSG

cGMP Clean Steam On Demand

WATER TECHNOLOGIES



Your Clean The POI

Applications

- Up to 6 barg Clean Steam for autoclave steam supply
- SIP (Sterilization In Place), bio reactors, make up vessels
- Sterile facility HVAC humidification
- Lyophilizer sanitization

Quantity and Quality of steam

- Standard units available between 50 - 10,000 kg/hr
- Rapid response steam production
- Low velocity, droplet free steam production via internal labyrinths
- Integrated thermal degasser for non condensable gases removal, in compliance with HTM 2010, 2031 & EN285 compliance

Service & support


- Local support & service from our global offices
- Yearly service & protection plans

Flexibility & choice

- Vertical and horizontal (Kettler) steam generators
- Additional condenser units for small scale, simultaneous steam & WFI production
- Siemens or Allen Bradley PLC, with large touchscreen panel & SCADA option
- Electric or steam heated units, integrated pre-treatment, RO, CEDI & UF for custom build packages



Lean Steam Needs... CLARIS Solution



Standard Features

Mechanical

- > ASME BPE piping
- > Steam sample point EN285 compliance
- > Thermal insulation
- > Stainless steel frame and control panel IP 54
- > Surface finishing Ra<0.6 µm
- > Feed water pump
- > Drain cooling system

Functional

- > PID pressure and flow control
- > Automatic blow down
- > Clean steam available from 3 to 6 bar

Controls and Instrumentation

- > PLC control + HMI interface
- > Automatic pressure, temperature and level controller

Validation and Documentation

- > Operating manual in English, qualification documentation in English

Optional Features

Mechanical

- > Electropolishing Ra<0.4 µm
- > Feed water tank
- > Clean Steam outlet check valve
- > Non compensated conductivity meter with automatic sample condensing and cooling system
- > Integrated thermal degasser
- > Membrane degasser

Controls and Instrumentation

- > SCADA supervision system (2 month operating data recording) / HMI in 4 language + printer (only interface required)

Validation and Documentation

- > DQ, IQ, OQ, PQ protocols
- > Operating manual



POLARIS - Service & Support

All POLARIS solutions are designed in accordance with GAMP, cGMP, ISPE and FDA guidelines and will meet the product quality specifications of all of the world's major pharmacopeia, including the USP and Ph Eur, giving you peace of mind and compliance assurance, wherever your facility is.

POLARIS systems are backed by a comprehensive range of service maintenance products.

Standardised Performance Qualification Maintenance Contracts (PQMC) are tailored to your system and ensure continuing compliance.


Scheduling service on a pre-planned basis coupled with time-based replacement of specific parts and consumables significantly reduces the risk of downtime. This approach enables us to guarantee the quality and value of your system for a lifetime.





Polaris CSG Capacity @3barg

CSG Model



POLARIS CSG Treated Water Quality

Conductivity	< 1.3 μ S/cm @ 25° C
TOC	< 500 ppb
Bacterial Endotoxins	< 0.25 EU
Bacteria	< 10 CFU / 100 ml
Nitrate	< 0.2 ppm
Heavy Metals	< 0.1 ppm

Services Required

Feed Water Temperature	15-25° C
Feed Water Pressure 1	1 < P < 6 bar
Power Supply	380/480 V; 3 Phase; 50/60 Hz
Compressed Air	6-8 bar
Water Drainage	By gravity
Cooling Water	15° C (if necessary)


Feed Water Requirement (Minimum)

Potable Water	
Total Hardness	< 0.1° F (1 ppm as CaCO ₃)
Conductivity	< 5 μ S/cm
Silica	< 1 ppm

Material Specification

Evaporating Columns	Inox 316L ASME BPE
Heat Exchanger (Pre-heater)	Inox 316L (EN 1.4435) ASME BPE
Heat Exchanger (Condenser)	Inox 316L ASME BPE
Feed Pump	Inox 316
Support Frame	Inox 304
Pipeline and Fittings	Inox 316L (EN 1.4435) ASME BPE
Control Panel	Inox 304
Valve	316L/EPDM FDA approved
Sealing and Gaskets	PTFE
Pipe Welding	Orbital

Resourcing the world



Veolia Water Technologies

L'Aquarène • 1 place Montgolfier • 94417 Saint-Maurice Cedex • France
tel. +33 1 45 11 55 55 - fax +33 1 45 11 55 50

www.veoliawatertechnologies.com